
FP-3020-OPS-DT

Flat-Panel Desktop Display for Honeywell TDC 2000 Stations

*A low-maintenance, long life upgrade
for your Operator Stations*



A high quality replacement display

This industrial LCD flat-panel display was designed as a desktop replacement for the CRT-based monitors used in Honeywell's TDC 2000 Basic and Enhanced Operator Stations. To install, attach the coaxial cables from the operator station to the adapter provided, plug in the power cable, and the display is ready for service.

Bright image, durable screen

The delicate LCD plastic surface is protected by a glass antiglare panel attached to the front of the display. This durable surface protects the LCD from the wear scratches that any plastic surface eventually suffers after repeated cleaning (or touching with fingers, pencils, or sharp objects). The antiglare treatment of the glass combined with the inherent low-glare characteristics of a flat display results in a high-contrast display that is easy on the eyes.

Low maintenance

The solid-state design of the flat-panel TFT LCD display provides inherent reliability, low power consumption, and low maintenance. This LCD technology is expected to last twice as long as CRT-based monitors. Setup adjustments are accomplished using control buttons located on the side of the frame.

Specifications

Viewable Area: 20.1" diagonal (19.5" w x 15" h x 3.5" d, without stand)

Viewing Angle: 170° horizontal, 170° vertical

Power Consumption: 449 watts, 110VAC/240VAC

Display modes supported: VGA 640x480 through VESA 1280x1024, includes Basic and Enhanced Operator Station scan frequency. BNC adapter included.

Contrast Ratio: 700:1

Operating Environment: Temperature 0-50°C,

Weight: 13.4 kg, 29.5 lb



WESTERN PROCESS COMPUTERS, INC.
2033 W. NORTH LANE, SUITE 14
PHOENIX, AZ 85021

Phone: 602-997-7245
Fax: 602-997-7248
info@westernprocess.com
www.westernprocess.com