
FP-3020X-DT

Flat-Panel Desktop Display for Honeywell UWS & Micro Stations

*A low-maintenance, long life upgrade
for your Universal Stations*



A high quality replacement display

This industrial LCD flat-panel display was designed as a direct replacement for the CRT-based monitors used in Honeywell's Universal Workstation or TDC Micro Station with EPDG or TPDG video. The display is available with or without an infrared touch screen. To install, simply connect the power cable, video cable, and (optional) touch screen cable to mating connectors on the new display.

Integrated flat touch screen

The FP-3020X-DT can be ordered with a flat infrared touch screen mounted to the front of the display. This option is referred to as the FP3020XTS-DT. The touch screen is mounted a few millimeters from the display surface, and eliminates "false picks" sometimes seen with the old touch screen because of its distance from the screen.

Bright image, durable screen

The delicate LCD plastic surface is protected by a glass anti-reflective panel attached to the front of the display. This durable surface protects the LCD from the wear scratches that any plastic surface eventually suffers after repeated cleaning (or touching with fingers, pencils, or sharp objects). The anti-reflective treatment of the glass combined with the inherent low-glare characteristics of a flat display results in a high-contrast display that is easy on the eyes.

Low maintenance

The solid-state design of the flat-panel TFT LCD display provides inherent reliability, low power consumption, and low maintenance. This LCD technology is expected to last twice as long as CRT-based monitors. Setup adjustments are accomplished using control buttons located on the side of the frame.

Specifications

Viewable Area: 20.1" diagonal (19.5" w x 15" h x 2.8" d, without stand)

Viewing Angle: 170° horizontal, 170° vertical

Power Consumption: 51 watts, 110VAC/240VAC

Display modes supported: VGA 640x480 through VESA 1280x1024, includes EPDG scan frequency. 15-pin connector, 9-pin and BNC adapters included.

Contrast Ratio: 700:1

Operating Environment: Temperature 0-50°C,

Weight: 13.4 kg, 29.5 lb



WESTERN PROCESS COMPUTERS, INC.
2033 W. NORTH LANE, SUITE 14
PHOENIX, AZ 85021

Phone: 602-997-7245
Fax: 602-997-7248
info@westernprocess.com
www.westernprocess.com